

Rugged-Reliable PoC Network Radio



Support LTE(4G)/WCDMA(3G)/GSM (2G) Network

- Worldwide Communication Range
- 1.8 Inch Color LCD Display
- Group Call and Individual Call
- Support REAL PTT Platform



SE600

PoC Network Radio

<http://www.sfecom.cn>

Main Features

- Support LTE(4G)/WCDMA(3G)/GSM(2G) Network
- Worldwide Communication Range
- 1.8 Inch Color LCD Display
- Group Call and Individual Call
- Support REAL PTT Platform
- With Functional Dispatching System
- GPS Function Optional
- Li-ion Battery Capacity 5200mAh
- Emergency Alarm Function
- Superb Clear and Powerful Audio Output

General/Technical Specifications

Model	SE600	SE600A
Working Voltage	DC3.7V	
Working Mode	Semi-Duplex	
Working Temperature	-20 ~ +60 °C	
Storage Temperature	-30 ~ +80 °C	
Battery Capacity	5200mAh	
Antenna Impedence	50Ω	
Audio Output	500mW	
Dimension	52*33*102mm	
Weight	Approx 220g(Battery & Antenna Included)	
Operation System	Linux	Android
Bluetooth	No	Yes
WIFI	No	Yes
GPS	Optional	
Frequency Range	LTE_FDD: B1/B3/B7/B8/B20	LTE_FDD: B1/B3/B5/B7/B8/B20
	WCDMA: B1/B8	WCDMA: B1/B2/B5/B8
	GSM: B3/B8	GSM: B2/B3/B5/B8*
	Other Bands Customized	
RF Power	≤30dBm	
RX Sensitivity	LTE ≤ -96 dBm	LTE ≤ -96 dBm
	WCDMA ≤ -108 dBm	WCDMA ≤ -108 dBm
	GSM ≤ -108 dBm	GSM ≤ -108 dBm

Above specifications are tested according to TIA/EIA-603.
Above specifications are subject to change without any notice due to technology enhancement.

Standard Accessories



Optional Accessories



SFE Quanzhou SFE Electronic Technology Co.,Ltd
Address: No.15, Chenggong Rd., Daping Industrial Area, Fengze, Quanzhou, Fujian 362000, China

SFE retains the right to change the product design and specifications without notices. If any printing mistake occurs, SFE will not bear the relevant responsibilities.

© 2018 SFE Electronic Technology Co.,Ltd.All Rights Reserved.

Your Local Dealer